




Trefinos
Maxium[®]

TECHNICAL SPECIFICATIONS

STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachlorophenol's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at trefinos@trefinos.es



CHARACTERISTICS		VALUES		SPECIFICATION	METHOD
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56923
	DIAMETER	Nom. value	mm	± 0,3	UNE 56923
PHYSICAL	DENSITY	290	Kg/m ³	± 40	UNE 56922
	HUMIDITY	6	%	± 2	UNE 56926
	RESIDUAL DUST	0,001	g/stopper	Maximum	UNE 56923
MECHANICAL	DIMENSIONAL RECOVERY (5')	91	%	Minimum	MI 98 IN CC
	COMPRESSION FORCE	140	daN	± 15	88 IN CC
	EXTRACTION TORQUE	30	daN · cm	± 4	MI 99 IN CC
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Maximum	UNE 56929
MICROBIOLOGIC	BACTERIA	30	UFC/stopper	Maximum	UNE 56923
	MOLD AND YEAST	10	UFC/stopper	Maximum	UNE 56923
SPME/ GC/ MS ANALISIS	2,4,6 –TCA,	1,9	ng/L	Maximum	UNE 56930
	2,3,4,6 – TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina		ng/L	< LD	External
SENSORY	SENSORY DEVIATIONS	AQL 0.65. Method: Water maceration.			

The products used for the manufacturing the product do not contain genetically modified organisms (GMOs) or allergens.

